



Battery powered LCD monitor with cable-free RF link

Housed in a robust IP65 sealed aluminium casing, and so effectively showerproof, EZ-ROAM is *the* "go any where" field monitor for every day use in the real world. Powered by rechargable batteries or 9 to 18V external power, expect about 8 hours use with a freshly charged 100 Watt/hour pack. 1 of 4 RF channels is SW selected for operation on the Licence-free* 2.4GHz band, enabling other EZ-ROAM Users independent operation. *DIVERSITY* operation + extra gain gives impressive radio link performance. *RX Video OP* + *Video IN* on BNC. Stereo Audio is looped from the camera's HP OP, through the EZ-ROAM's 10mW (CE "legal") transmitter which draws a miniscule 35mA from the camera. Our 500mW higher power transmitter draws 270mA from a 9 to 18V dc supply via 4 pin Hirose, and provides monaural operation. 1/4" bush mounting kit is available for the camera. A tough anti-glare 2mm polycarbonate scratch-resistant window protects the LCD; recessed controls provide contrast, brightness & saturation control. 16:9/4:3 LCD switchable aspect. Horiz & Vert FLIP display modes. An EZ-ROAM tilt 'n twist gimble mount is available to aid viewing from *any* angle.

* In most parts of the world

Outline Specification

- * Only 225L x 140W x 50D.
- * 16:9 native, 4:3 switchable.
- * PAG or V-Lock battery mount.
- * Fully sealed LCD panel, IP65.
- * PAL & NTSC auto-switching.
- * Clean and bright pictures
- * Stereo Headphone output.
- * Gimble mount option.

- * Radio link OP & local IP on BNC
- * Switch selectable RF channel
- * LCD: 480 x 234 400CdM'
- * Wide viewing angle
- * Negligable picture cut-off
- * Temp: -20 +60' (-30 +80' store)
- * Weight: Tx 110Gm Rx 1.05KGm
- * Highly affordable

Murraypro

8, Glamorgan Road, Hampton Wick, KT1 4HP UK